BEXRO
ESSENTIAL



FS Series

FS | Floorstand Digital Signage

- *High Brightness 500 nits LCD Panel*
- *4K Resolution 3840x2160*
- *Tempered Glass Frontal IP65 Protection*
- *RK3568 Quad Core, 2/32GB RAM/ROM, Android 11*
- *IR Remote Controller easy turn on/off*
- *Network WIFI Dual Band, LAN Port*

FS-T | Floorstand Interactive Signage

- *All Same Spec with FS Series + Touchscreen*
- *RK3568 Quad Core, 4/32GB RAM/ROM, Android 11*
- *Model FS-TR for Infrared Touchscreen*
- *Model FS-TC for Capacitive Touchscreen*
- *BEXRO CMS Cloud manage touchscreen*






Model	FS43 FS43-TR (Infrared TS) FS43-TC (Capacitive TS)	FS49 FS49-TR (Infrared TS) FS49-TC (Capacitive TS)	FS55 FS55-TR (Infrared TS) FS55-TC (Capacitive TS)	FS65 FS65-TR (Infrared TS) FS65-TC (Capacitive TS)
Display				
Backlight type	LED	LED	LED	LED
Screen size	43 inch	49 inch	55 inch	65 inch
Active area, H × V (mm)	940 × 528	604 × 1074	680 × 1209	804 × 1428
Resolution	1080 × 1920	2160 × 3840 (4K)	2160 × 3840 (4K)	2160 × 3840 (4K)
Aspect ratio	16:9	16:9	16:9	16:9
Brightness	500 nits	500 nits	500 nits	500 nits
Color	8 bit, 16.7M	8 bit, 16.7M	8 bit, 16.7M	8 bit, 16.7M
Contrast ratio	1200:1	1200:1	1200:1	1200:1
Response time	8 ms	8 ms	8 ms	8 ms
Viewing angle (H/V)	178° / 178°	178° / 178°	178° / 178°	178° / 178°
Backlight life	30,000 hrs (min.)	50,000 hrs (min.)	50,000 hrs (min.)	50,000 hrs (min.)
Touchscreen				
Optional	3mm Tempered Glass/ Infrared Touchscreen 10 Points/ Capacitive Touchscreen 10 Points			
Internal Player (Android)				
OS	Android 11	Android 11	Android 11	Android 11
CPU	Quad-core RK3568	Quad-core RK3568	Quad-core RK3568	Quad-core RK3568
RAM	2GB (4GB for FS-T)	2GB (4GB for FS-T)	2GB (4GB for FS-T)	2GB (4GB for FS-T)
ROM	32GB	32GB	32GB	32GB
Network	Wi-Fi 2.4/5GHz	Wi-Fi 2.4/5GHz	Wi-Fi 2.4/5GHz	Wi-Fi 2.4/5GHz
I/O interface	USB × 2, HDMI Input × 1, LAN Port, Audio Out			
Software	USB Auto Player, PC LAN Mode, Mobile Phone Direct, Bexro Cloud CMS			
Power				
Power supply	100–240V, 50/60Hz	100–240V, 50/60Hz	100–240V, 50/60Hz	100–240V, 50/60Hz
Power consumption	≤ 65W	≤ 65W	≤ 120W	≤ 150W
Environment				
Operating temperature	0°C to 50°C	0°C to 50°C	0°C to 50°C	0°C to 50°C
Operating humidity	20% to 80% RH	20% to 80% RH	20% to 80% RH	20% to 80% RH
Physical				
Bezel L/R / T/B (mm) *	25 / 25	27 / 30	27 / 32	38 / 43
Body, W × H × D (mm) *	604 × 1800 × 460	669 × 1800 × 78.2	733 × 1900 × 78.2	878 × 2000 × 78.2
Package, W × H × D (mm) *	1860 × 680 × 160	1870 × 770 × 160	1960 × 840 × 160	2060 × 990 × 160
Package weight (1 pc) *	37kg	45kg	51kg	65kg
Other				
Installation method	Floorstand	Floorstand	Floorstand	Floorstand
Operation method	Remote control	Remote control	Remote control	Remote control
Shell material	Metal	Metal	Metal	Metal

*Remark : * All Specifications and product descriptions may change without notice.*